

December 12, 1996

PN 9442B

Ms. Nancy Wagner IPSCO 2900 South 21st Avenue Broadview, Illinois 60153



SUBJECT:

Limited Subsurface Soil Investigation

2424 Wisconsin Avenue Downers Grove, Illinois

Dear Ms. Wagner:

Enclosed are two copies of the Limited Subsurface Soil Investigation completed by Carlson Environmental, Inc. (CEI) for the above-referenced site. A summary of our findings is located on Page 4 of this report.

If you have questions or would like additional information please contact me or Edward Garske at (312) 346-2140.

It was a pleasure to complete this assignment on your behalf.

Sincerely,

CARLSON ENVIRONMENTAL, INC.

Melanie L. Luna

Environmental Technician

Alane Jona

enclosures

EPA Region 5 Records Ctr.



LIMITED SUBSURFACE SOIL INVESTIGATION

2424 Wisconsin Avenue Downers Grove, Illinois

Prepared by
CARLSON ENVIRONMENTAL, INC.
312 West Randolph Street
Suite 300
Chicago, Illinois 60606
(312) 346-2140

Project No. 9442B December 12, 1996

Melanie L. Luna

Environmental Technician

Edward E. Garske, CHMM

Vice President of Operations



TABLE OF CONTENTS

1.0	INTRODUCTION	•			•		•					•		
2.0	BACKGROUND													
	2.1 Site Description													
	2.2 Purpose of Investigation					•		•		•	•		•	•
3.0	SOIL INVESTIGATION		 											
	3.1 Sampling Methodology		 						 ,					
	3.2 Laboratory Analytical Results													
4.0	SUMMARY AND RECOMMENDATIONS		 											

ATTACHMENTS

ATTACHMENT A - Figures and Tables

ATTACHMENT B - Soil Boring Logs

ATTACHMENT C - Laboratory Analytical Report

Page 1

1.0 INTRODUCTION

The objective of this Limited Subsurface Soil Investigation was to address environmental issues identified by Carlson Environmental, Inc. (CEI) in the Phase I Environmental Assessment site inspection, for the property located at 2424 Wisconsin Avenue, Downers Grove, Illinois (Figure One, Attachment A).

According to available information, staining was observed along the south wall of the loading dock area where the facility's air compressor discharge is located, and near two aboveground storage tanks (ASTs). The staining travels west to catch basins which are reportedly cleaned out on a regular basis. In addition, CEI observed staining outside the north wall of the site building along the north wall of the warehouse area. Finally, two gasoline pump islands were observed on the north side of Burnside Construction Company located adjacent to and east of the subject property. No underground storage tanks (USTs) were registered for this site (Figure One, Attachment A).

On December 3rd and 4th, 1996, CEI returned to the site to collect soil samples from under the loading dock's concrete floor surrounding the air-compressor discharge, outside the north wall of the site building in the vicinity of the drum storage area and along the eastern property boundary line closest to the two gasoline pump islands located at Burnside Construction Company. This is a report summarizing CEI's investigation and findings.

2.0 BACKGROUND

2.1 Site Description

The site covers approximately 4.0 acres and contains one building, asphalt-paved parking areas an undeveloped area and a gravel-covered area. The rectangular, one-story slab-on-grade structure has concrete construction. The site was constructed in approximately 1977. Prior to construction of the site building, the property was undeveloped. Currently, the site building is occupied by Bison Gear & Engineering Corporation which utilizes the facility to manufacture gear motors. Operations include stamping, painting, and assembly of cast steel and paper products for forming and shipping gear motors.

2.2 Purpose of Investigation

On December 3rd and 4th, 1996, CEI returned to the site to collect soil samples from beneath the concrete floor surrounding the air-compressor's discharge, outside on the north side of the building where staining was observed and along the eastern property



Page 2

boundary line closest to the two gasoline pump islands identified at Burnside Construction Company. The purpose of this investigation was to determine if the subsurface soils had been impacted by volatile organic compounds (VOCs), polynuclear aromatic hydrocarbons (PNAs) or benzene, toluene, ethyl benzene and xylene (BTEX) compounds.

3.0 SOIL INVESTIGATION

3.1 Sampling Methodology

On December 3rd and 4th, 1995, Melanie Luna, and Phil Hoeksema of CEI conducted the sampling activities at the subject site. During the investigation, CEI drilled through the concrete floor at four (4) locations and through a gravel covered area in the parking lot. The exact sampling locations were determined based on field observations and are depicted on Figure Two in Attachment A.

Boreholes LD-1 and LD-2 were emplaced around the air compressor's discharge located in the loading dock area. Boreholes LD-4 and LD-5 were emplaced outside the north wall of the site building in the vicinity of the drum storage area. Borehole LD-3 was emplaced at the easternly property line closest to the two gasoline pump islands located at Burnside Construction Company (Figure Two, Attachment A). Boreholes LD-1, LD-2, LD-4 and LD-5 were advanced to a depth of 5 feet below the ground surface (bgs). Borehole LD-3 was advanced to a depth of fifteen feet bgs.

At each of the four covered area, approximately 6-inches of concrete was encountered. Beneath the concrete were sandy and silty clays. Soil boring logs detailing the materials encountered at each borehole are included in Attachment B. After drilling through the concrete floor and gravel-covered area with a 6-inch diameter diamond tipped corebarrel, a geoprobe was used to continuously sample the soils. All soil samples were examined for visual evidence of contamination and screened with a photoionization detector (PID). The PID is an effective device for identifying areas where VOCs (e.g., oils, solvents, gasoline constituents, etc.) may exist. However, the PID does not identify specific compounds or their concentrations.

All down-hole drilling equipment was cleaned prior to use and between each borehole, and the spoon samplers was cleaned with an Alconox® soap solution between each sample.



Page 3

Based on the results of field screening (PID measurements, odors and visual observations, etc), 5 soil samples were submitted for laboratory analyses. The samples selected depicted the greatest potential for contamination. Samples: LD-1E (5') and LD-2A (1') were submitted for PNA analysis using EPA Method 8310 and BTEX analysis using EPA Method 8021. Sample: LD-3D (7-9') was submitted for BTEX analysis using EPA Method 8021. Samples: LD-4A (1') and LD-5B (3') were submitted for PNA analysis using EPA Method 8310 and VOC analysis using EPA Method 8260.

Soil samples collected for chemical analyses were placed in laboratory supplied glass jars equipped with teflon-lined lids. The soil samples were immediately labeled and placed into an iced insulated cooler upon collection. Upon completion of the site activities, selected soil samples were shipped to Great Lakes Analytical for chemical analyses based on PID measurements. At all times, the samples were maintained under standard chain-of-custody procedures.

After the soil samples were collected, the concrete cores were placed back into the holes and approximately 1 to 2 inches of "quick drying cement" was used to fill in the remaining void which was subsequently leveled to the surrounding surface.

Field activities were performed following CEI's corporate Health and Safety procedures and guidelines, including the use of proper personal protection equipment.

3.2 Laboratory Analytical Results

All samples were submitted to Great Lakes Analytical of Buffalo Grove, Illinois, for analysis. No PNAs were detected in samples LD-1E and LD-2A above laboratory detection limits. Low levels of PNAs were detected in samples LD-4A and LD-5B, however these concentrations are below the Illinois Environmental Protection Agency's (IEPAs) Tiered Approach to Corrective Action Objectives (TACAO) Tier 1 Industrial/Commercial Route Values for migration to Class I Ground Water or Industrial/Commercial Ingestion pathways (Table One, Attachment A).

No BTEX was detected in samples LD-3D above laboratory detection limits. Low levels of BTEX was detected in samples LD-1E and LD-2A, however these concentrations are below the IEPA's TACAO Tier 1 Industrial/Commercial Route Values for migration to Class I Ground Water pathway (Table Two, Attachment A).

Low levels of VOCs were detected in samples LD-4A and LD-5B, however these concentrations are below the IEPAs TACAO Tier 1 Industrial/Commercial Route Values for migration to Class I Ground Water or pathway (Table Three, Attachment A).



Page 4

A copy of the complete laboratory report along with the chain of custody is included in Attachment C.

4.0 SUMMARY AND RECOMMENDATIONS

The following is a summary of the Limited Subsurface Soil Investigation conducted by CEI at the property located at 2424 Wisconsin Avenue, Downers Grove, Illinois for the staining issues and gasoline pump islands identified in the Phase I Environmental Assessment report dated November 6, 1996.

The purpose of this investigation was to confirm if the site soils have been impacted by a release of contaminants. A total of five soil borings were emplaced at the subject site. Two soil samples were collected from the loading dock area beneath the concrete floor surrounding the air-compressor's discharge and analyzed for PNAs and BTEX. Two soil samples were collected from outside the north wall of the building near the overhead door and analyzed for PNAs and VOCs. One soil boring was collected from the eastern property boundary line closest to the two gasoline pump islands identified at Burnside Construction Company and analyzed for BTEX.


The laboratory reports indicate that low levels of PNAs, BTEX and VOCs were detected in several samples analyzed. However, none of the concentrations exceeded the IEPAs TACAO cleanup objectives.

According to the samples collected and analyzed, there does not appear to be significant contamination in the areas sampled.



ATTACHMENT A

Figures and Tables



LEGEND


● 55-GALLON DRUMS FILLED WITH SCRAP METAL

PALLETS

- PAD-MOUNTED TRANSFORMERS
- **♦** FUEL PUMPS

LD-58 • APPROXIMATE SAMPLING LOCATIONS







CARLSON ENVIRONMENTAL, INC. 312 WEST RANDOLPH STREET CHICAGO, ILLINOIS 60606 (312) 346-2140

FIGURE TWO APPROXIMATE BOREHOLE LOCATIONS

BISON GEAR & ENGINEERING CORP. Downers Grove, Illinois

 Drawn By: MLL
 Project No. 9442B
 Scale: No Scale

 Checked By:
 Date: 12/04/96
 Size A

TABLE ONE:

Soil Sample Analytical Results PNA (EPA Method 8310 - mg/kg) 2424 Wisconsin Avenue

December 4, 1996

	Tier I Soil Remediation		Sample ID		
Compound	Objectives for Industrial/Commerci al Properties *	LD-1E	LD-2A	LD-4A	LD-5B
Benz(a)anthracene	2	ND	ND	0.20	ND
Benzo(a)pyrene	8	ND	ND	1.6	ND
Benzo(b)fluoranthene	5	ND	ND	0.071	0.014
Benzo(g,h,i)perylene	NE	ND	ND	0.052	ND
Benzo(k)fluoranthene	49	ND	ND	0.60	ND
Chrysene	160	ND	ND	0.39	ND
Dibenzo(a,h)anthracene	0.8	ND	ND	0.020	ND

Notes:

 $\bullet = IEPA$ Soil Cleanup Objectives established for the protection of Class I ground water or Industrial/Commercial Ingestion pathways

mg/kg = Milligrams per kilogram (parts per million)

ND = not detected NE = not established

TABLE TWO:

Soil Sample Analytical Results BTEX (EPA Method 8021 - mg/kg) 2424 Wisconsin Avenue

December 4, 1996

	Tier I Soil Remediation	Sample ID		/ Depth		
Compound	Objectives for Industrial/Commercial Properties *	LD-1E	LD-2A	LD-3D		
Benzene	0.30	0.0037	0.002	ND		
Toluene	12	0.0081	ND	ND		
Ethyl benzene	13	0.010	ND	ND		
Xylenes	190	0.034	0.018	ND		

Notes:

*= IEPA Soil Cleanup Objectives established for the protection of Class I ground water.

mg/kg = Milligrams per kilogram (parts per million)

ND = not detected

TABLE THREE:

Soil Sample Analytical Results VOC (EPA Method 8310 - mg/kg) 2424 Wisconsin Avenue

December 4, 1996

_	Tier I Soil Remediation Objectives for Industrial/Commercial Properties *	Sample ID / Depth		
Compound		LD-4A	LD-5B	
Chloroethane	NE	ND	0.25	
cis 1,2-Dichloroethene	0.4	ND	0.0084	
Ethyl benzene	13	ND	0.010	
Toluene	12	0.038	0.32	
Trichloroethylene	0.06	0.007	0.011	
Total Xvienes	190	0.019	0.051	

Notes:

EPA Soil Cleanup Objectives established for the protection of Class I ground water.
 mg/kg = Milligrams per kilogram (parts per million)

ND = not detected

NE = not established



图图

ATTACHMENT B

Soil Boring Logs

MAJOR DIVISIONS					TVDICAL NAMES
	MAJOR DIV			_	TYPICAL NAMES
	GRAVEL AND	CLEAN GRAVELS	000	GW	Wolf-graded gravels, gravel-send mixtures, little or no fines
LS	GRAVELLY SOILS	Little or no fines	000	GP	Poorly-graded gravels, gravel-send mixtures, title or no fines
COARSE-GRAINED SOILS lace ten 60% larger than No 200 leve titte	More then 50% of coarse fraction is larger than No. 4 seven size	GRAVELS WITH		GM	Silty gravets, gravel-eand-oilt mixtures
ANE	(10, 4 and 122	With over 12% fines		GC	Clayey gravels, gravel-eand-clay mixtures
-GR		SAND AND SANDY SOILS More than 20% of course fraction is smaller than No. 4 steve size CLEAN SAND Little or no tines SANDS WITH FINES With over 12% fines		sw	Well-graded sends, gravelly sends, little or no fines
ARSI	SANDY SOILS			SP	Poorly-graded cande, gravelly cends, little or no fines
8	course fraction is amader than			SM	Sity-cands, send-oilt mixtures
	No. 4 abrid #24			sc	Clayey sands, sand-clay mixtures
ဟု	04.70			ML	inorgenic sitis and very fine sands, rect flour, ethy or citypy fine sands or citypy eiths, with elight planticity
		SILTS AND CLAYS Liquid limit less than 50%		CL	inorganic clays of low to modium plasticity, gravelty clays, sandy clays, sity clays, ison clays
INED (OL	Organic alits and organic silty clays of low planticity
FINE-GRAINED SOILS More than 50% stradder than No. 200 above alase	CII TC AI	SILTS AND CLAYS		МН	knorganis silis, micaneous or distomaceous fine sand or silty sollo
	1	valor then 50%		СН	inorganic clays of high plasticity, fet clays
FI				у ОН	Organic clays of medium to high plasticity, organic sits
	HIGHLY ORGAN	IIC SOILS		ή PT	Pest, humus, swamp solls with high organic content

UNIFIED SOIL CLASSIFICATION SYSTEM

 \sum - Bulk or classification sample

Sample preserved for possible analysis

First-encountered ground water level (saturation)

Static ground water level

Standard Penetration Test

Push sample (thin walled sampler "Shelby Tube")

OVA - Organic Vapor Analyzer, including both the PID and FID

Photoionization Detector, (Microsp H-200) calibrated to 100 ppm isobusylene standard with a 10.2 eV lamp PID

FID .

Flamelonization Detector (Century 128) celebrated with 95 ppm methans

Counts - Blows required to drive a standard spirtspoon sampler 6 inches with a 140 pound hammer free faling 30 inches Blow

counts for S & H samplers are converted to appro-"equivalent" SPT N valued (n = 0.5 x S & H blows per foot)

"n" value . Number of blows required to advance the spiritspoon sample

two 6 inch increments felling 6 inches of seating

KEY TO BORING LOG

CARLSON ENVIRONMENTAL, INC.



312 West Randolph Street Chicago, Illinois 60606 (312) 346-2140

Soil Classification Chart Key To Test Data

1				
ı	Date 9-8-05	Orann By P Berys	Revised Cate	Sheet of

Carlson Environmental, Inc. 312 West Randolph Street Suite 300 Chicago, IL 60606

Log of Boring LD-1 Bison Gear & Engineering Corp. 2424 Wisconsin Avenue Downers Grove, Illinois

Sheet 1 of 1

Job Number: 9442B

Phone (312) 348-2140 Fax (312) 348-8958 Elevation: Drier: Carlson Environmental, Inc. Date/Time Started: 12/03/96 0905 Dritt Method: Geoprobe Date/Time Completed: 12/03/96 1017 Sample Method: 11/4-Inch Diameter Plastic Sleeve Depth to Water: ft. BGS Depth to Rock: ft. BGS Borehole Diameter: 1 3/4 in. Total Depth: 5 ft. BGS Logged By: MLL Checked By: PAH Sample Interval (feet) PID (units) Recovery (in) L09 Sample No. (time) Blow Counts Depth (feet) Materials Description Remarks Graphic CONCRETE LD-IA 1.5 NA (0908) Light brown SANDY CLAY (CL-SC), soft to medium stiff, moist axidation observed (D-18) 2 1.2 NA Color changed to brown with fine gravel 2. oxidation Brown, gravelly SILTY CLAY (CL), medium stiff, observed LD-1C (0925) 3 0.0 NA axidation Brown CLAYEY SAND, fine grained sand seam observed LD-10 (0937) Brown, gravelly SILTY CLAY (CL), medium stiff, 4 0.0 NA maist oxidation observed LD-1E (1018) 5 121.0 NA stiff nolfablico observed Boring terminated at 5 feet bgs. 6 7 8 9

Carlaon Environmental, Inc. 312 West Randolph Street Sulte 300 Chicago, IL 60606 Phone (312) 346-2140 Fax (312) 346-8958

Log of Boring LD-2 Bison Gear & Engineering Corp. 2424 Wisconsin Avenue Downers Grove, Illinois

Sheet 1 of 1

Job Number: 94428

Elevation: Date/Time Started: 12/03/96 0940 **Driller:** Carlson Environmental, Inc. Date/Time Completed: 12/03/96 1144 Drill Method: Geoprobe Sample Method: 1 1/4-Inch Diameter Plastic Sleeve Depth to Water: ft. BGS Depth to Rock: ft. BGS Total Depth: 5 ft. BGS Borehole Diameter: 1 3/4 in. Logged By: MLL Checked By: PAH Sample Interval (feet) PID (units) Recovery (in) aphic Log Sample No. (time) Blow Counts Depth (feet) Materials Description Remarks ŏ CONCRETE LO-2A ı 5.7 NA (0845) Light brown SANDY CLAY (CL-SC), soft to medium stiff, moist oxidation Brown STLTY CLAY (CL), hard, moist to dry, observed trace coarse sand LD-28 4.7 NA 2 (1100) 2 gxidation observed LD-2C (1125) 3 1.8 NA oxidation abserved LD-2D (1127) 4 18.7 NA calar changed to dark brown, dry, line coarse sand LO-2E 5 NA 7.0 (1148) Boring terminated at 5 feet bgs. 6 7 -8 9

Carlson Environmental, Inc.
312 West Randolph Street
Suite 300
Chicago, IL 60606
Phone (312) 346-2140 Fax (312) 346-6956

Log of Boring LD-3 Bison Gear & Engineering Corp. 2424 Wisconsin Avenue Downers Grove, Illinois

Sheet 1 of 1

Job Number: 94428

Elevation: Dritter: Rock & Soil Drilling Corp. Date/Time Started: 12/03/96 1355 Drill Mathod: Geoprobe Date/Time Completed: 12/03/96 1555 Sample Method: 11/4-Inch Diameter Plastic Sleeve Depth to Water: ft. BGS Depth to Rock: ft. BGS Total Depth: 15 ft. BGS Checked By: PAH Borehole Diameter: 1 3/4 in. Logged By: MLL Sample Interval (feet) PID (units) Recovery (in) Graphic Log g. Blow Counts Sample N (time) Depth (feet) Materials Description Remarks CONCRETE Brown SILTY CLAY (CL), soft to medium stiff with coarse sand LD-3A 1-3 151.0 NA (1414)3. Brown SILTY CLAY (CL), medium stiff to stiff. LD-38 medium coarse sand with fine gravel 204.0 4 3-5 NA (1428) LD-3C 5-7 31.9 NA (1440) saturated with coarse gravel LD-3D 8 7-9 187.0 NA (1455)LD-3E (1530) 9-11 10 21.8 NA color changed to gray/brown LD-3F 12 11-13 38.6 NA (1555) 13 LD-3G (1805) 14 13-15 31.8 NA 15 Boring terminated at 15 feet bgs. 16 17 18 19 20Carison Environmental, Inc.
312 West Randolph Street
Suite 300
Chicago, IL 80606
Phone (312) 348-2140 Fax (312) 346-8958

Log of Boring LD-4 Bison Gear & Engineering Corp. 2424 Wisconsin Avenue Downers Grove, Illinois

Sheet 1 of 1

Job Number: 94428

Elevation:

Date/Time Started: 12/04/96 0820 Orller: Carlson Environmental, Inc. Date/Time Completed: 12/04/96 0839 Drill Method: Geoprobe Sample Method: 1 1/4-Inch Diameter Plastic Sleeve Depth to Rock: 1t. BGS Depth to Water: 1t. BGS Borehole Diameter: 1 3/4 in. Checked By: PAH Total Depth: 5 ft. BGS Logged By: MLL Sample Interval (feet) PID (units) Recovery (in) Graphic Log Sample No. (time) Blow Depth (feet) Materials Description Remarks CONCRETE LD-4A (0825) 0-1 480.0 NA Brown/gray SILTY CLAY (CL), still with trace fine sand and gravel Solvent odor detected color changed to green/gray with trace gravel LD-48 1-3 84.8 NA (0833)Solvent adar detected color changed to gray, moist LD-4C 113.0 3-5 NA (0841)Salvent adar detected Boring terminated at 5 feet bgs. 6 7. 8 9

Carlaon Environmental, Inc.
312 West Randolph Street
Suite 300
Chicago, IL 60606
Phone (312) 348-2140 Fax (312) 346-895

Log of Boring LD-5 Bison Gear & Engineering Corp. 2424 Wisconsin Avenue Downers Grove, Illinois

Sheet 1 of 1
Job Number: 94428

Phone (312) 348-2140 Fax (312) 346-6958 Elevation: Date/Time Started: 12/04/96 0850 Driller: Carison Environmental, Inc. Dr期 Method: Geoprobe Date/Time Completed: 12/04/96 0910 Sample Method: 1 1/4-Inch Diameter Plastic Sleeve Depth to Rock: 1t. BGS Depth to Water: ft. BGS Borehole Diameter: 1 3/4 in. Total Depth: 5 ft. BGS Logged By: MLL Checked By: PAH Sample Interval (feet) PID (units) Recovery (in) Blow Counts Sample N (time) Depth (feet) Materials Description Remarks apple Ö CONCRETE LD-5A (0855) 582.0 0-1 NA Brown/gray SILTY CLAY (CL), still with trace line sand and gravel Salvent adar detected color changed to brown, soft, moist LD-58 0.886 1-3 NA color changed to brown/gray, medium stiff with (0904)trace coarse sand Solvent odor detected LD-5C (0912) 3-5 351.0 NA Solvent adar detected Boring terminated at 5 feet bgs. 6 7 -8-9



ATTACHMENT C

Laboratory Analytical Reports



1380 Busch Parkway . Buffalo Grove, Illinois 60089

Soil

(847) 808-7766 FAX (847) 808-7772

rison Environmental, Inc.

Client Project ID:

9442B, Bison Gear & Eng. Corp.

Received:

Sampled: Dec 3, 1998 Dec 4, 1998

W. Randolph Street cago, IL 60606

Matrix Descript: Analysis Method:

EPA 5030/8021

Analyzed:

ention: Melania Luna

First Sample #: 612-0589

HANDER OF THE SECOND SE

Dec 6, 1996 Dec 10, 1996 Reported:

BTEX ANALYSIS (EPA 8021)

Sample Number	Sample Description	Benzene mg/kg (ppm)	Toluene mg/kg (ppm)	Ethyl Benzene mg/kg (ppm)	Xylenes mg/kg (ppm)
: 612-0589	LD-1E	0.0037	0.0081	0.010	0.034
612-0\$90	LD-2A	0.0020	N.D.	N.D.	0.018
÷ 612-059 1	LD-30	N.D.	N.D.	N.D.	N.D.

Desction Limits: 0.0020 0.0050 0.0050 0.0150

lytes reported as N.D. were not present above the stated limit of detection.

EAT LAKES ANALYTICAL

FW. Keeley oratory Director

8120589.CAR <1>



1380 Busch Parkway . Buffaio Grove, Illinois 60089

(847) 808-7786 FAX (847) 808-1772

Client Project ID: 94428, Bison Gear & Eng. Corp. ison Environmental, Inc. Sampled: Dec 3. W. Randolph Street Sample Descript: Soil: LD-1E Received: Dec 4, 1996 cago, IL 60606 Dec 5, 1998 Analysis Method: **EPA 8310** Extracted: ention: Melanie Luna Lab Number: 612-0589 Analyzed: Dec 5, 1 Reported: Dec 10, 1

POLYNUCLEAR AROMATIC HYDROCARBONS (EPA 8310)

Aphyte	Detection Limit mg/kg		Sample Results mg/kg
Adnaphtriene	1.2		N.D.
Adenaphthylene	0.66		N.D.
Arthracene	0.86	*******************************	N.D.
Bezo (a) anthracene	0.0087	*******************************	N,D.
B 20 (a) pyrene		************************************	N.D.
Baizo (b) Nuoranthene			N.D.
Bazo (ghi) perylane		***************************************	N.D.
Bazo (k) fluoranthene		***************************************	N.D.
Citysene		*****************************	N.D.
Digenzo (a,h) anthracene		***************************************	N.D.
File ranthene		***************************************	N.D.
Flabrene		***************************************	N.D.
Ineno (1,2,3-cd) pyrene			N.D.
Na hthalene		***************************************	N.D.
Primanthyène		**************************************	N.D.
Pylane			N.D.

Analytes reported as N.D. were not present above the stated limit of detection.

GREAT LAKES ANALYTICAL

Kenn W. Kheley Lateratory Director

6120589.CAR <4>



800-4770 GREHT LHKES HIML

1380 Busch Parkway . Buffalo Grove, Illinois 60089

(847) 808-7766 FAX (847) 806-7772

ison Environmental, Inc. 94425, Bison Gear & Eng. Corp. Client Project ID: Sampled: W. Randolph Street Sample Descript: Soil: LD-2A Received: Dec 4, 1 |cago, IL 60606 Analysis Method: **EPA 8310** Extracted: Dec 5, 1996 ention: Melanie Luna Lab Number: 612-0590 Dec 5, 1 Analyzed: Dec 10, 1996 Reported: PRESENTED THE RESERVE THE PROPERTY OF THE PROP

POLYNUCLEAR AROMATIC HYDROCARBONS (EPA 8310)

Aplyte	Detection Limit mg/kg		Sample Results mg/kg
Adinaphthene	1.2	}*************************************	N.D.
Adanaphthylene	0.66	******************************	N.D.
Authracene	0. 56		N.D.
Bazo (a) anthracene	0.0087	**4***************************	N.D.
B a zo (a) þyrane	0.015	**************************	N.D.
Bezo (b) fluoranthene		P14034404001040104050550250400000000000000000	N.D.
Bezo (ghi) perylene		***************************************	N.D.
Bezo (k) fluoranthene		1870040040180000000000000000000000000000	N.D.
Claysene	0.10	******************************	N.D.
Differzo (4,h) anthracene	0.020	**************************************	N.D.
Fleranthene	0.66	*************	N.D.
Flabrene	0.14	***************************************	N.D.
in no (1,2,3-cd) pyrene		***************************************	N.D.
Na hthalene		***************************************	N.D.
Plananthrene	. 0,66	*******************************	N.D.
Pyline	0,18	***************************************	N.D.

Ar tytes reported as N.D. were not present above the stated limit of detection.

GREAT LAKES ANALYTICAL

Keen W. Keeley Lasoratory Director

8120589.CAR <5>



图图

1380 Busch Parkway . Buffalo Grove, Illinois 60059

(847) 808-7766 FAX (847) 808-1772

4.1

Sampled: ison Environmental, Inc. 9442B, Bison Geer & Eng. Corp. Client Project ID: Dec 3. W. Randolph Street Soff: LD-4A Sample Descript: Received: Dec 4, 1 cago, L 60606 Analysis Method: **EPA 8310** Extracted: Dec 5, 1996 ention: Melanie Luna Leb Number: 612-0592 Analyzed: Dec 5, 1996 Reported: Dec 10, 1996

POLYNUCLEAR AROMATIC HYDROCARBONS (EPA 8310)

Apriyle	Detection Limit mg/kg		Sample Results mg/kg	
Admaphthene			N.D.	1
Agenaphtriyiene		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	N.D.	1
Aghracene		*****************************	N.D.	1
STREET, STREET, SECTION	The first and the Colon of the Assessment		ATTACA STATE OF STATE	
	A Comment of the second of the			46
22 予預があるすがは、12.70.00				30
				: 3

2	The first of the state of the s	. in the same of	or and a standard designs.	
FI	pranthene	0.86		N.D.
FI	Prens.,4	0.14	*******************	N.D.
In	eno (1,2,3-cd) pyrene	0.029	*****************************	N.D.
N	hthalene	0.66	***********************	N.D.
P	nanthrene	0.66	*4 \$0 *1 \$0 3 \$ 1 3 4 \$0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	N.D,
Py	ene	0.18	***************************************	N.D.

Artilytes reported as N.D. were not present above the stated limit of detection.

GEAT LAKES ANALYTICAL

Kelley Laboratory Director

6120589.CAR <6>



1380 Busch Parkway . Buffalo Grove, Illinois 80089

(847) 808-7766 FAX (847) 808-2772

Bampled:

Calson Environmental, Inc. 31: W. Rahdolph Street Cacago, IL 60606 America: Melanie Luna

Client Project ID: 9442B, Bison Gear & Eng. Corp. Sample Descript: 8oll: LD-5B
Analysis Method: EPA 8310
Lab Number: 612-0593

Received: Dec 4, 1996 Extracted: Dec 5, 1996 Analyzed: Dec 5, 1996 Reported: Dec 10, 1996

Dec 3, 1996

. . =

POLYNUCLEAR AROMATIC HYDROCARBONS (EPA 8310)

a lyte	Detection Limit mg/kg		Sample Results mg/kg
naphthene	1.2	*******************************	N.D.
naphthylene	0.66	************************	N.D.
Markene	0.86	1468881	N.D.
Senzo (a) anthracene	0.0087	1328510194004840448448444	N.D.
3 (a) pyrene	0.015	14281,,2,,2,,2,,,,,,,,,,,,,,,,,,,,,,,,,,	N.D.
A TELL MARKET STATE OF THE STAT		THE STATE OF THE S	THE RESERVE OF THE PARTY OF THE
Beizo (ghi) perylene	0.051		N.D.
3 (k) fluoranthene	0.011		N.D.
Caysene.	0.10	**,;*********************************	N.D.
Disenzo (4,h) anthracene	0.020		N.D.
Flabranthene	0.88		N.D.
Fi gorene	0.14	*****************************	N.D.
neno (1,2,3-cd) pyrene	0.029	.44	N.D.
Nighthalene		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	N.D.
Plananthrene		***************************************	N.D.
Pare	0.18	******************************	N.D.

Applytes reported as N.D. were not present above the stated limit of detection.

GEAT LAKES ANALYTICAL

Kelley Laboratory Director

6120589.CAR <7>



1380 Busch Parkway . Buffalo Grove, Illinois 80089

(547) 608-7788 FAX (847) 808-7772

Ison Environmental, Inc. W. Randolph Street cago, L 60608 ention: Melanie Luna

94428, Bison Geer & Eng. Corp. Client Project ID: Sample Descript: Soll: LD-4A

Analysis Method: **EPA 8260** 612-0592

Sampled: Dec 3, 199 Received: Dec 4, 1996

Analyzed: Dec 9, 1996 Reported: Dec 10, 1996

VOLATILE ORGANICS by GC/MS (EPA 8260)

Lab Number:

plyte	Detection Limit µg/kg		Sample Results µg/kg
tone	25		N.D.
2210.	5.0		N.D.
modichloromethane	5.0		N.D.
moform	5.0	**********	N.D.
momethane	5.0		N.D.
Ltanone	10	***************************************	N.D.
bon disulfide	5.0	****************************	N.D.
bon terachioride	5.0		N.D.
probenzene		***************************************	N.D.
brodibromomethane	5.0		N.D.
proethane	5.0	***************************************	N.D.
Noroethyl vinyl ether		***************************************	N.D.
oroform	5.0		N.D.
promethane	5.0		N.D.
Dichloroethane	5.0	1414141444	N.D.
Dichloroethane			N.D.
Dichloroethene		***************************************	N.D.
1,2-Dichloroethene	5.0	******	N.D.
s-1,2-Dichloroethene	5.0	***************************************	N.D.
Dichloropropane			N.D.
ff ,3-Dichloropropene		***************************************	N.D.
s 1,3-Dichloropropene			N.D.
Mbenzene		***************************************	N.D.
exanone	. 10	***************************************	N.D.
hylene chloride	. 5.0		N.D.
Bethyl-2-pentanone		***************************************	N.D.
Fene	5.0		N.D.
2,2-Tetrachloroethane	. 5.0		N.D.
achlorpethene	. 5.0	171194444444444444444444444444444444444	N.D.
1-Trich proethans	. 5.0		N.O.
2-Trichloroethane	. 5.0	***************************************	N.D.
			Fig. 25 Carriers
i noronuoromethane	5.0	****************************	N.D.
in 1 acetate	. 10	************************	N.D.
ind chloride	5.0		N.D.

EAT LAKES ANALYTICAL

W. Keeley oratory Director

6120589.CAR <2>



1380 Busch Parkway - Buffalo Grove, Illinois 80089

(847) 808-7786 FAX (847) 808-1772

Calson Environmental, Inc. 3 & W. Randolph Street Calcago, IL 80606 Atlantion: Melanie Luna

Client Project ID: 94428, Bison Gear & Eng. Corp. Sample Descript: Soil: LD-58

Analysis Method: EPA 8260 Lab Number: 612-0593 Sampled: Dec 3, 199 Received: Dec 4, 199

Analyzed: Dec 9, 1996 Reported: Dec 10, 1996

VOLATILE ORGANICS by GC/MS (EPA 8260)

inte	Detection Limit		Sample Results
· ·	µg/kg		µg/kg
ltone	25	***************************************	N.D.
zene	5.0		N.D.
modicialoromethane	5.0		N.D.
moform	5.0		N.D.
momethane	5.0	*******************************	N.D.
Litanone	10		N.D.
bon digulfide	5.0	***********************	N.D.
bon tetrachloride	5.0	***************************************	N.D.
probenzene	5.0	*****************************	N.D.
prodibnomomethane	5.0	/*************************************	N.D.
	Charles and the contract of		
Noroethy Viny ether	10	Haller and the second s	N.O.
proform	5.0	***************************************	N.D.
promethane	5.0		N.D.
Dichloroethane		***************************************	N.D.
Dichiorgethene.	5.0		N.D.
Olchloroethene	•••		N.D.
The action of the second second			AND THE PERSON OF THE PERSON O
a-1,2-Dichloroethene	5.0	***************************************	N.D.
Dichlocopropens		***************************************	N.D.
M 3-Dichloropropene	5.0	***************************************	N.D.
s 1,3-Dichloroproperie	5.0	***************************************	N.D.
	THE REAL PROPERTY.		
examone	10	CONTRACTOR SANCTOR SAN	N.D.
hylene chloride	-	***************************************	N.D.
ethyl-2-pentanone		***************************************	N.D.
ene			N.D.
2,2-Tetrachioroethane			N.D.
achloroethene			N.D.
			NOW WITH THE PARTY OF THE PARTY
1-Irichloroethane		100 to	N.D.
2-Trichloroethane		***************************************	N.D.
TOTO (POPOMET) and	5.0	The second second second control of the	N.O.
acetate.	4.5		N.D.
	. 5.0 <u> </u>		N.D.

An lytes reported as N.U. were not present above the stated limit of detection.

GEAT LAKES ANALYTICAL

Keeley Laboratory Director

6120589.CAR <3>

CARLSON ENVIRONMENTAL, INC. 312 W. Randolph St.	Chicago, IL 60606 (312) 346-2140		
SAMPLERS THE CHANGE (MELANIE L. LUNA			
SAMPLE DESCRIPTION SAMPLE DESCRI	REMARKS		
LD-1E 12/3 1019 V Sample collected from 5'	2 11 6120589		
LD-2A 12/3 0945 V Sample Collected from 11	- 2 VV 6120590		
, LD-3D 12/3 H55 V Jample Collected from 7-9'	6120591		
. LD-4A 2/4 pass V Sample collected from 1'	2 1 6120592		
. LD-5B 12/4 0904 Jample collected from 3'	2 1 6120593		
;			
•			
Selame Tour 12/4/20 MR Horash Deserting Paradity Description 1/4/96 MR Horash 12/4/86 MR Horash 12/4/86	PLEASE FAX RESULTS TO: MELANIE LUNIA @ (312) 346-6956		
Reinsuched by strains (Opigiting Resinsed by Latinsatory by It grows	ME # PLEASE FAX NUT 12/10/96 2:00pm		

U.S. ENVIRONMENTAL PROTECTION AGENCY

MAR 3 1 2004

OFFICE OF REGIONAL COUNSEL